



Technical data

Model	Duty mode	Power Supply Type	Self-lock	Motor type	Force lb-ft	Fastest full traveling time	Control Unit	Rated Power	Rated Current	Weight
EOE2000	On/Off	3PH380VAC	Yes	S2	1475 lb-ft	102s	Control A or B	200W	12A	106lb

Model	Duty mode	Power Supply Type	Self-lock	Motor type	Force lb-ft	Fastest full traveling time	Control Unit	Rated Power	Rated Current	Weight
EOE2000	On/Off	1PH220VAC	Yes	S2	1475 lb-ft	102s	Control A or B	200W	12A	106lb

Model	Duty mode	Power Supply Type	Self-lock	Motor type	Force lb-ft	Fastest full traveling time	Control Unit	Rated Power	Rated Current	Weight
EOE2000	On/Off	24VDC/ Wide voltage up to 500VAC	Yes	S2	1475 lb-ft	102s	Control B	200W	12A	106lb




Mechanical Dimensions-Integrated type (Unit: inch)

Mode	Direct Connection														Base and Level			
	W1	W2	W3	W4	H1	H2	H3	H4	Φ D		Md		Flange	Weight lb	L	W	H	Weight lb
									ENISO	MSS	ENISO	MSS						
									5211	SP-101	5211	SP-101						
Unit: inch								Unit: inch										
EOE2000	15.63	10.32	17.44	1.81x1.81	15.59	3.35	5.00	7.17	Φ5.51 Φ6.05	Φ5.51 Φ6.50	M0.63 M0.79	5/8-11 3/4-10	FA14 (FA16)	106	-	-	-	-

Note: “-” means Not available


Direct connection type:







INTELLIGENT TYPE WIRING DIAGRAMS


3-phase AC, 380V (Modulating)




3-phase AC, 380V (on-off)



1/3-phase AC 100-500V((Modulating)




1/3-phase AC 100-500V (on-off)




Explosion-proof
IP68 double seal

DC,24V(Modulating)




DC,24V(on-off)






Split-type Electrical Wiring



1. The sensor signal cable shall be 14-core cable with shield; The sectional area of the line shall be 0.5mm^2 , and the length of the line shall not exceed 10m; depending on the site condition
2. The motor connection line adopts the cable with a sectional area of 0.5mm^2 ,
3. Pay carefully attention to the wiring between the electronic unit and the actuator to avoid malfunctioning;
4. Cable conforming to the national standard IEC 60227 and IEC 60245 shall be preferred.
5. In high temperature environment, please use high temperature cable, incoming device(connector), cable protection shell, etc. that meet the requirements;
6. This wiring diagram is only between the electronic unit and the actuator. For control wiring, please refer to the wiring diagram of conventional products in Easytrac operational manual.



Profibus DP Wiring Diagram 286 board




Ontrac electric actuators can optionally support


- Profibus- DP fieldbus protocol with additional code of "286". A Profibus network segment can connect up to 32 Ontrac electric actuators. The transmission speed of Ontrac electric actuators can be 9.6kbps ~ 1500kbps
- Foundation fieldbus and is Foundation ITK inter-operability certified. It is fully compliant with IEC61158-2 standard.
- Modbus RTU protocol communications at a baud rate up to 38.4kbps/s. Our factory default speed is 9.6kbps/s giving a 1.5km maximum distance between nodes. We use a master / slave query response polling cycle with CRC (Cyclic Redundancy Check).
- HART Communication Protocol (Highway Addressable Remote Transducer) connectivity. HART allows use of conventional 4 – 20 mA wiring.



Modbus/Hart Wiring Diagram 288 board



Foundation Fieldbus Wiring Diagram 290 board



EOE2000	Non-thrust	
Mechanical interface type	Splined bore	Splined bore
Flange size (ISO 5211)	FA14	/
Maximum square spindle diameter (inch)	1.77X1.77	/

Code Model	Flange	d1	d2		d3		d5	T1	T2	d4
			Standard size	Factory default	Factory default	Max stem Diameter (keyway)				
EOE2000	FA14	Ø7.80	Ø5.51	Ø5.51	Ø0.39	Ø 1.89(0.55)	Ø2.87	3.35	0.61	4-M0.55 deep 0.95in

The technical drawing consists of two views of a handwheel assembly. The left view is a cross-section showing the internal structure, including a central shaft with a keyway, a hub, and a flange. Dimensions are labeled: $T1$ for the total thickness, $T2$ for the hub thickness, $\phi d3$ for the inner hole diameter, $\phi d5$ for the keyway diameter, $\phi d2$ for the hub outer diameter, and $\phi d1$ for the flange outer diameter. The right view is a top view of the flange, showing a circular plate with four bolt holes. The bolt holes are labeled $d4$ and $\phi d3$. The bolt holes are spaced at 45° intervals. A dashed line indicates the center of the flange. A note at the bottom right states "Parallel to handwheel axis".



Specifications

Voltage supply	3-phase: 380±5%, 50/60Hz±5% 1-phase: 110/220V±10%, 50/60Hz±5% 100-500VAC (Wide voltage Optional) 24VDC
Duty mode	On-off and Inching (EOE Type) S2-15 min Modulating, EME Type S4-25%, 1200times/hr.
Motor specification	F Class DC motor and AC motor
Internal control power supply	24 VDC
Input Signal	24 VDC (Optional for 220/110VAC) for on-off 4-20 mA (Analogue Input) for modulating Profibus-DP or Modbus, Ethernet, Foundation Fieldbus (all optional)
Output Signal	1.) 30VDC 5A or 220/110VAC 5A (Dry contact 4 SPST) Open/close, State indicator, Alarm 2.) 4-20 mA (Analogue Output) 3.) Profibus-DP or MODBUS, Hart, Ethernet, Foundation Fieldbus (all optional),
Intermediate position	Optional
Dead zone	0.5% (0.5 ~ 15% adjustable, default is 2%)
Enclosure protection	IP67 as standard IP68 (optional)
Explosive protection	Ex db eb IIC T4 Gb (optional)
Fail safe	Battery back (optional)
Safety Integrity level (optional)	SIL2&3 Electric actuators with configurable safety functions: Stay put or Emergency shut-down (ESD) open or close on demand.
Ambient conditions	1) Temperature: -20°C to 65°C, -40°C and -60°C optional 2) Humidity: in up to 100% humidity 3) Air media: corrosive, flammable and explosive gas, optional coating
Heater	Optional
Anticondensation	Anticondensation heater included
Coating	Double layer powder coating, C5-M (ISO12944 Marine Optional)
Color	RAL9005 is standard, available colors on request
CE standard  And others	1) EN 61000-6-4: 2007, EN 61000-6-2: 2005 2) EN 61000-3-2: 2006 +A1:2009+A2: 2009, EN 61000-3-3: 2008 3) EN 60204-1: 2006+A1: 2009 4) ATEX: SCA23ATEX209X,
Cable connection	2*M25 for cable Φ10-Φ16